


TAURUS R-410A 60HZ WINDOW ROOM AIR CONDITIONER COOLING ONLY / ELECTRIC HEATER

YWF(H)E 18 to 24 ZH2DHCOR3



Auto Air Swing



Air Filter



Silent Operation



High Efficiency
Protected
Compressor



60 Hz

60 Hz



Electric Heater



Ease of
Installation



Multi-Speed Fan
Motor



UP TO
52°C

High Ambient
Operation



R
410A

Environment
Friendly R410A



Specification

York Set Model			YWFE18ZH2DHCOR3	YWHE18ZH2DHCOR3	YWFE24ZH2DHCOR3	YWHE24ZH2DHCOR3
Power supply		Ph/V/Hz	1/230/60	1/230/60	1/230/60	1/230/60
Rated Cooling(T1)	Capacity	Btu/h	17,200	17,200	21,500	21,500
	Capacity	kW	5.0	5.0	6.3	6.3
	Input	kW	1.685	1.685	2.108	2.108
	Running current	A	7.40	7.40	9.40	9.40
	EER	W/W	3.0	3.0	3.0	3.0
	EER	Btu/hW	10.20	10.20	10.20	10.20
Rated Cooling(T3)	Capacity	Btu/h	14,400	14,400	18,000	18,000
	Capacity	kW	4.2	4.2	5.3	5.3
	Input	kW	2.025	2.025	2.500	2.500
	Running current	A	8.90	8.90	11.10	11.10
	EER	W/W	2.08	2.08	2.11	2.11
	EER	Btu/hW	7.10	7.10	7.20	7.20
Electric Heating	Capacity	kW	/	3.5	/	3.5
Indoor air flow		m ³ /h	740	740	900	900
Indoor noise level (Sound pressure level)		dB(A)	56/55/54	56/55/54	64/62/60	64/62/60
Indoor dimension	Unit (WxDxH)	mm	660/691/428	660/691/428	660/780/428	660/780/428
	Packing (WxDxH)	mm	740/781/525	740/781/525	740/860/525	740/860/525
Indoor weight	Net	kg	52.5	53	61	61.5
	Gross	kg	57.5	58	66	66.5
Refrigerant	Type	-	R410A	R410A	R410A	R410A
Refrigerant pipe	Liquid side/Gas side	mm	/	/	/	/
	Additional refrigerant charge	g	/	/	/	/

Nominal testing conditions @T1:

Cooling - Indoor 80.6°F DB / 66.2°F WB (27°C DB / 19°C WB) & Outdoor 95°F DB / 75.2°F WB (35°C DB / 24°C WB)

Nominal testing conditions @T3:

Cooling - Indoor 84.2°F DB / 66.2°F WB (29°C DB / 19°C WB) & Outdoor 114.8°F DB / 75.2°F WB (46°C DB / 24°C WB)

*This product is coming with holding refrigerant charge from the factory. Refrigerant charge must be checked before startup to assure design performance.

*We reserve the right to change features and/or specifications anytime without notice and without incurring any liability.



INSTALL CONFIDENCE

Johnson Controls, the Johnson Controls logo, YORK are registered trademarks of Johnson Controls, Inc in the United States of America and other countries. Other trademarks used herein may be trademarks or registered trademarks of other companies.

FOR MORE INFORMATION CONTACT JOHNSONCONTROLS.COM